TECHNICAL DATA SHEET



EM 1409 54% Active Emulsion of Amine Functional Polydimethylsiloxane

Method Value Description **Property**

This product is an emulsion of amine functional **Product** polydimethylsiloxane.

Key Features Appearance White liquid Extended performance Ionicity Non-ionic

Effective in low concentrations Solids Content (%) 54 % Excellent wetting/spreading on surfaces

Easily dispersed in water with minimal agitation **Addition Rates**

Key Applications

Dosage - 1 0.1 - 1% Release agent

Casting Max Storage Temperature 40 °C / 104 °F Extrusion

40 lb. pails, 441 lb. drums, **Application** Packaging 2205 lb. totes, and tanker

Storage

EM 1409 is a 54% active emulsion of amine functional Shelf Life 12 mths polydimethyl siloxane. The high molecular weight amino

dimethicone emulsion demonstrates excellent dilution stability at very low concentrations and is chemically inert. This emulsion was developed as an effective release agent for a variety of applications which include rubber, casting, and extrusion.

Use and Cure Information

Rubber treatment

To optimize the dispersion of this emulsion into the final formulation, it is recommended to add it slowly at the end of the procedure at a temperature below 40 °C (104°F) with continuous mixing or stirring

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

This product is not intended for pharmaceutical use.

Revision Date 12 Feb 2024

Revision No 14

Download Date 29 Apr 2024