TECHNICAL DATA SHEET



EM 2750I 60% Active Emulsion of Organic Polymers and Polydimethylsiloxane

Test

12 mths

Property		Value
. ,	Method	
Product		
Appearance		White liquid
Ionicity		Non-ionic
Solids Content (%)		60 %
рН		7.5
Storage		
May Storage Temperature		40 °C / 104 °F
wax olorage remperature		
Packaging		40 lb. pails, 441 lb. drums, and 2205 lb. totes
	Ionicity Solids Content (%) pH Storage Max Storage Temperature	Product Appearance Ionicity Solids Content (%) pH Storage Max Storage Temperature

Application

Description

EM 2750I is a 60% active emulsion of a complex blend of organic polymers and dimethyl polysiloxane fluids. This product is easily diluted with water, demonstrates excellent dilution stability at very low concentrations and is chemically inert. EM 2750I may be formulated with either a cationic or an anionic system since it is made with nonionic emulsifiers. It can also be formulated with an antistat upon customer request. This emulsion has been specially formulated for roll-to-roll high speed printing. The active polymers seal the ink into the paper, provide improved shine and elminates the appearance of printing flaws.

Shelf Life

Use and Cure Information

· Printing and foundry release

To optimize the dispersion of this emulsion into the final formulation, it is recommended to add it slowly at the end of the procedure at a temperature below 40 °C (104 °F) with continuous mixing or stirring.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

This product is not intended for pharmaceutical use.

Revision Date 12 Feb 2024

Revision No 6

Download Date 29 Apr 2024