

HANSA CARE 8017 D Modified siloxane as an ingredient for Home and Car Care.

Description

Aminosiloxanes are Siloxanes modified with Nitrogen groups. The modification degree lead to an optimal performance in aqueous or solvent borne formulations for home and car care applications. These products are excellently suited for a use in polishes, wax formulations and drying aids in automatic or manual car wash and provide for perfect drying characteristics including a good water repellence and excellent gloss.

Key Features

- Water repellency, Beading effect
- Durability
- Enhances Gloss
- Wax effect

Key Applications

- Rinse Aids
- Car Polishes
- Spray Waxes

Application

HANSA CARE 8017 D is applied as hydrophobic component with an additional gloss and smoothness in dryer formulations for automatic car wash. This makes the polymer ideal for use in formulations with wax effects. HANSA CARE 8017 D can also be used in spray wax formulations or paint polishes.

Health & Safety

Health & Safety

Safety Data Sheet available on request.

Packaging

Drums and bulk containers. Please contact our sales department for more information.

Property

Product

Appearance

Chemistry

Ionicity

MIT Free

Nitrogen Content (%)

Non-Volatile Content (%)

Ultralow cyclic content

Viscosity

Test Method

Value

Transparent, slightly opaque liquid
Aminosiloxane

Cationic

Yes

Approx. 1.7

Approx. 100

No

Brookfield **800-4.000 cP**

Addition Rates

Dosage - 1

0.5 – 10.0% in polishes and sealants

Dosage - 2

3.0 – 10.0% in high-gloss rinse aid formulations with wax effect

Dosage - 3

0.5 – 5.0% in spray wax formulations

Storage

Max Storage Temperature

40 °C / 104 °F

Min Storage Temperature

4 °C / 39 °F

Shelf Life

24 mths

Revision Date 29 Apr 2021
Revision No 1
Download Date 09 May 2024