TECHNICAL DATA SHEET



HANSA CARE 8645 D Macroemulsion of a modified siloxane as an ingredient for Home and Car Care.

Shelf Life

Min Storage Temperature

Description

Aminosiloxanes are Siloxanes modifed with Nitrogen groups. The modification degree lead to an

optimal performance in aqueous or solvent borne formulations for home and car care applications.

These products are excellently suited for a use in polishes, wax formulations and drying aids in automatic or manual car wash and provide for perfect drying characteristics including a good water repellence and excellent gloss.

- **Key Features**
- Water repellency
- Durability
- Improves Gloss and Color depth .
- Smoothness and Softness
- **Key Applications**
- Car Care
- Leather and Furniture Care
- Kitchen and Sanitary Cleaner Fabric Care

Application

HANSA CARE 8645 D can be used as a water-repellent additive for water based care product formulations which improves as well gloss and color depth. It gives a strong softening effect in fabric care formulations.

Health & Safety

Health & Safety

Safety Data Sheet available on request.

Packaging

Drums and bulk containers. Please contact our sales department for more information.

Revision Date	29 Apr 2021
Revision No	1
Download Date	29 Apr 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product	
specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet.	

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com

Property	Test Method	Value
Product		
Appearance		White to slightly yellow liquid
Chemistry		Macroemulsion of an aminosiloxane
Ionicity		Cationic
MIT Free		Yes
Non-Volatile Content (%)		Approx. 40
Ultralow cyclic content		Yes
pH (10% solution)		5.0 - 7.0
Addition Rates		
Dosage - 1		1.0 - 5.0% in polishes
Dosage - 2		1.0 - 4.0% in fabric care
Storage		
Max Storage Temperature		40 °C / 104 °F

40 °C / 104 °F 4 °C / 39 °F 12 mths