

## HANSA CARE HTC

### Inorganic/Organic polymer based on Si-Ceramic-Sol-Gel Chemistry as an ingredient for Home and Car Care products.

Description	Property	Test Method	Value
Silicone resins are reactive polymers to enhance durability and water repellency of many formulations. The Silicone resins can be used in combination with reactive Aminosiloxane to formulate high quality sealants for car care or long lasting impregnation agent for mineral surfaces. Further applications of Silicone resins are car polishes, spray waxes, impregnation agents for kitchen worktops and for wood.	<b>Product</b>		
	Appearance		Clear fluid
	Chemistry		Silicone resin
	Ionicity		Non-ionic
	MIT Free		Yes
	Non-Volatile Content (%)		95
	Ultralow cyclic content		Yes
<b>Key Features</b>			
<ul style="list-style-type: none"> <li>• Very easy to apply and suitable for do-it-yourself application</li> <li>• Forms a transparent hard and semi-flexible film</li> <li>• Excellent resistance with good adhesion</li> <li>• Hydrophobic</li> </ul>	<b>Addition Rates</b>		
	Dosage - 1		High end sealants 20-70%
	Dosage - 2		Easy to use sealants 10 - 30%
<b>Key Applications</b>			
<ul style="list-style-type: none"> <li>• Glass sealants</li> <li>• Plastic sealant</li> <li>• Car sealants</li> </ul>	<b>Storage</b>		
	Max Storage Temperature		40 °C / 104 °F
	Shelf Life		12 mths
<b>Application</b>			
For optimum performance, we recommend non-polar solvents such as aliphatic hydrocarbons, isododecane or D5. If polar solvents are required, anhydrous isopropanol, which can be combined with the non-polar solvent, is recommended.			
Lasts on glass 2-6 months depending on weather conditions and washing cycles.			
<b>Health &amp; Safety</b>			
Safety Data Sheet available on request.			
<b>Packaging</b>			
Drums. Please contact our sales department for more information.			

Revision Date      10 Jan 2024  
Revision No        19  
Download Date     09 May 2024