TECHNICAL DATA SHEET



ICM EM 1612 15% surfactant-free microemulsion of a unique amino-functional silioxane

D	es	cr	ip	tı	01	1
---	----	----	----	----	----	---

This product is a microemulsion of a unique aminofunctional silicone. The specialized aminosilicone is designed to quickly and effectively, hydrophobe and protect a variety of automotive surfaces.

Key Features

- · Surfactant free
- Adds extremely hydrophobic and protective clear coat to car surfaces
- Lasts up to 90 days before retreatment
- · Compatible with cationic, anionic, and nonionic surfactants

Key Applications

- Automotive Care
- Leather
- Fabric Care
- · Glass treatments

Use and Cure Information

This microemulsion can be used directly or diluted 10:1 in water while maintaining pH less than 6, with any common acid, for optimal stability and effectiveness.

- 1. Throughly clean automotive surfaces before use.
- 2. Apply using a foam generating lance or spray bottle.
- 3. For maximum effectiveness alow to dwell for 1-2 minutes.
- 4. Rinse vigorously to activate.
- 5. Repeat applications for increased durability and effectivness.

Property	Test Method	Value	
Product			
Appearance		Yellow, translucent liquid	
Chemistry		Aminosiloxane Emulsion	
MIT Free		Yes	
Non-Volatile Content (%)		15	
Ultralow cyclic content		No	
pH		4.5	
Addition Rates Dosage - 1		5-20%	
Storage			
Max Storage Temperature		40 °C / 104 °F	

4 °C / 39 °F

drums

12 mths

40 lb. pails or 441 lb.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Min Storage Temperature

Packaging

Shelf Life

Limitations

This product is not intended for pharmaceutical use.

Revision Date 21 Sep 2021

Revision No

Download Date 29 Apr 2024

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.