TECHNICAL DATA SHEET



ICM EM 1616 ECO 16% surfactant-free emulsion of unique amino-functional siloxane

Description This product is a microemulsion of a unique aminofunctional silicone. The specialized aminosilicone is designed to quickly and effectively, hydrophobe and protect a variety of automotive surfaces.	Property	Test Method	Value
	Product		
	Appearance		Yellow, translucent to hazy liquid
Key Features	Chemistry		Aminosiloxane Emulsion
 < 3% VOC Surfactant Free Adds extremely hydrophobic and protective clear coat to car 	MIT Free		Yes
	Non-Volatile Content (%)		16
surfaces	Ultralow cyclic content		No
 Facilitates rapid water sheeting and beading 	рН		4.5
Key Applications • Automotive Care	Addition Rates		
Leather	Dosage - 1		5-20%
Fabric CareGlass Treatments	Storage		

Application ICM EM 1616 ECO has been specially formulated to be a

surfactant free emulsion leaving only the active ingredients after drying. The unique amino-functional siloxane and additives

Min Storage Temperature 4 °C / 39 °F Shelf Life 12 mths

Max Storage Temperature

provide a durable crosslinked structure that hydrophobes a variety of materials. ICM EM 1616 ECO is a low VOC product, containing less

40 °C / 104 °F

Use and Cure Information

This microemulsion can be used directly or diluted 10:1 in water while maintaining pH less than 6, with any common acid, for optimal stability and effectiveness.

- 1. Throughly clean automotive surfaces before use.
- 2. Apply using a foam generating lance or spray bottle.
- 3. For maximum effectiveness alow to dwell for 1-2 minutes.
- 4. Rinse vigorously to activate.
- 5. Repeat applications for increased durability and effectivness.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

than 3%

This product is not intended for pharmaceutical use.

Revision Date 22 Mar 2024

Revision No.

Download Date 28 Apr 2024