## TECHNICAL DATA SHEET



## **ICM EM 1642** High-end nonionic emulsion of silicone crosspolymer

Description	Property	lest Valu	ıe
This product is a emulsion of a crosspolymer gel.	. reporty	Method	
Key Features	Product		
Excellent surface leather conditioner	Appearance	Milk	W
<ul> <li>Improves touch and surface slip</li> </ul>	Ionicity	Non	-io

Provides a light scattering matte effect **Key Applications** 

. . . . . . . . . . . .

Leather

Tires

Synthetic surfaces

Automotive surfaces

**Application** 

ICM EM 1642 is a emulsion of a crosspolymer gel that is designed for use on leather and other interior automotive surfaces to reduce glare and improve touch properties. ICM EM 1642 can also be used as a high end, long lasting slip aid for sliding windows and doors as well as an anti-squeak additive for automotive interiors.

**Use and Cure Information** 

This product is compatiable with aqueous systems and can be added directly to the formulation with minor agitation.

**Health & Safety** 

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

This product is not intended for pharmaceutical use.

**Revision Date** 21 Sep 2021

Revision No

Download Date 28 Apr 2024 Non-Volatile Content (%) 8 Ultralow cyclic content No Viscosity (cst) 100,000

**Addition Rates** 

Dosage - 1 0.5-25.0%

Storage

Max Storage Temperature 40 °C / 104 °F Min Storage Temperature 4 °C / 39 °F

32 lb. pails or 325 lb. Packaging

drums Shelf Life 12 mths