

## HANSA CARE 9020 D Modified siloxane as an ingredient for Home and Car Care.

### Description

The silicone hybrids are special silicone polymers combined with the organic polymer chemistry. Therefore it is possible to create with these polymers unique and outstanding effects in home-, fabric- and car care products.

### Key Features

- Water repellency
- Enhances Gloss and Color depth
- Durability

### Key Applications

- Car Polishes
- Sealants
- Treatments
- Leather Care

### Application

HANSA CARE 9020 D can be used in car and home care products to improve water repellency, color depth, durability, shine and gloss.

### Use and Cure Information

Stir before use.

### Health & Safety

Safety Data Sheets available on request.

### Packaging

Drums and bulk containers. Please contact our sales department for more information.

### Property

#### Product

Appearance

Chemistry

Ionicity

MIT Free

Non-Volatile Content (%)

Ultralow cyclic content

Viscosity

### Test Method

### Value

Colorless to yellowish liquid

Sugar modified Aminosiloxane

Cationic

Yes

Approx. 100

No

Brookfield 2,000 - 8,000 cP

### Addition Rates

Dosage - 1

1.0 - 5.0% in polishes

Dosage - 2

1.0 - 10.0% in vinyl and tyre care

Dosage - 3

1.0 - 5.0% in rinse aids

### Storage

Max Storage Temperature

40 °C / 104 °F

Min Storage Temperature

4 °C / 39 °F

Shelf Life

12 mths

Revision Date 13 Jun 2022

Revision No 9

Download Date 14 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet.

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

**CHT Germany GmbH:** Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: [info@cht.com](mailto:info@cht.com), Homepage: [www.cht.com](http://www.cht.com) / [www.cht-silicones.com](http://www.cht-silicones.com)