TECHNICAL DATA SHEET



HANSA MBC 37180

Mixture of OH-PDMS and reinforcing filler for producing condensation crosslinking silicones

Description CHTs masterbatches are a mixture of silica and polysiloxane.	Property Product	Test Method	Value
Addition of the masterbatch is a convenient method of incorporating silica into an elastomer formulation to increase	Color		Transparent
physical properties. The values for tensile, tear, and elongation	Non-Volatile Content (%)		> 99
typically increase commensurately with additional silica.	Shelf Life		12 mths
Masterbatchs are typically suited specifically for condensation or	Ultralow cyclic content		Yes
addition cure chemistries. The compositions are solvent-free and typically low in cyclic siloxane content.	Viscosity	Brookfield HTBD, 23	600000 cP
Key Features			
 containing silica 	Uncured Product		
 containing OH-Siliconepolymer 	Cure Type		Condensation cure
translucent			
 good mechanical properties 	Cured Product		
Key Applications	Density	DIN 53479	1.19 g/cm3
 Intermediate for condensation curing formulations 			
Use and Cure Information	Solubility		
Masterbatches are typically high viscosity and non-flowing. One	Solubility - Water		insoluble

must incorporate siloxane polymers of the appropriate chemistry

and viscosity profile to result in a flowable composition. Curing can be obtained with the addition of an appropriate crosslinker and catalyst system.

Health & Safety

Please observe our safety data sheets and the safety remarks on our container labels when handling our products. The dangerous goods regulations and the accident prevention regulations of the professional associations must be particularly observed. Keep the EC safety data sheet of the applied product at hand since it provides you with useful instructions for the safe use and disposal of the product as well as for actions to be taken in case of accidents.

Revision Date21 Feb 2023Revision No7Download Date14 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.