

## ICM EM 421 Ready to use ultra high molecular weight polydimethylsiloxane emulsion

### Description

This product is an industrial nonionic polydimethylsiloxane emulsion.

### Key Features

- Ready to use formula
- Compatible with nonionic, anionic, and cationic formulations
- Ultra high viscosity internal polymer for lubrication
- Uniformed deposition on surfaces

### Key Applications

- Industrial lubrication
- Leather conditioning
- Auto care
- Rubber treatment

### Application

ICM EM 421 is a 5% ready to use emulsion of a unique ultra high molecular weight polydimethylsiloxane fluid. ICM EM 421 is designed to be used in industrial mold release applications, slip additive for rubber release, and industrial coating where superior mar resistance and hydrophobicity is desired. This product is also an effective leather conditioner and has been used in automotive care, rubber treatment, mold release and printing applications.

### Use and Cure Information

To optimize the dispersion of this emulsion into the final formulation, it is recommended to add it slowly at the end of the procedure at a temperature below 40 °C (104 °F) with continuous mixing or stirring.

### Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

### Limitations

This product is not intended for pharmaceutical use.

### Property

#### Product

Appearance  
Ionicity  
Solids Content (%)  
pH

### Test Method

### Value

White liquid  
Non-ionic  
5 %  
5

#### Addition Rates

Dosage - 1

Ready to use in Industrial applications

#### Storage

Max Storage Temperature  
Packaging  
Shelf Life

40 °C / 104 °F  
40 lb. pails or 460 lb. drums  
12 mths

Revision Date      22 Nov 2021  
Revision No        7  
Download Date     14 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

**CHT Germany GmbH:** Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany  
Telephone: 07071/154-0, Fax: 07071/154-290, Email: [info@cht.com](mailto:info@cht.com), Homepage: [www.cht.com](http://www.cht.com) / [www.cht-silicones.com](http://www.cht-silicones.com)