

SILCO CT 5144 Low cyclic silicone non-ionic PDMS gum emulsion

Description

This product is a non-ionic industrial emulsion of extremely high molecular weight polydimethylsiloxane.

Key Features

- High solids emulsion of high molecular weight PDMS
- Low cyclic silicones
- Provides mar resistance and anti blocking properties
- Performs at low concentrations

Key Applications

- Water based paints, inks, and coatings
- Leather conditioning
- Rubber treatment
- Printing applications

Use and Cure Information

To optimize the dispersion of the product into the final formulation, it is recommended to add it slowly at the end of the procedure at a temperature below 40 °C (104 °F) with continuous mixing or stirring. Recommended use levels for conditioners is 1% to 5%.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

This product is not intended for pharmaceutical use.

Property

Product

Appearance	Light yellow paste
Ionicity	non-ionic
Solids Content (%)	80 %
pH	4.5

Storage

Max Storage Temperature	40 °C / 104 °F
Min Storage Temperature	4 °C / 39 °F
Shelf Life	12 mths

Revision Date	26 Mar 2024
Revision No	4
Download Date	14 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany
Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com